



- NOTES:
1. DRAWING IS REPRESENTATIVE OF TYPICAL PIPING SYSTEM AND DOES NOT ILLUSTRATE ALL COMPONENTS REQUIRED FOR A COMPLETE INSTALLATION. REFER TO ORDER SPECIFIC DOCUMENTATION FOR HUBBELL SCOPE OF SUPPLY
 2. REFER TO THE NX INSTALLATION AND OPERATION MANUAL FOR DETAILED INSTRUCTION.
 3. INSTALLER RESPONSIBLE FOR COMPLIANCE WITH ALL APPLICABLE CODES.

LEGEND

- | | | | | | |
|--|-----------------|--|-----------------------|--|---|
| | CIRCULATOR | | BACK FLOW PREVENTER | | FLOW SWITCH |
| | ISOLATION VALVE | | CHECK VALVE | | PRESSURE GAUGE |
| | UNION | | DRAIN VALVE | | FLOW DIRECTION |
| | STRAINER | | PRESSURE RELIEF VALVE | | THERMOSTAT OR TEMPERATURE PROBE WITH WELL |

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF THE ELECTRIC HEATER COMPANY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF THE ELECTRIC HEATER COMPANY IS PROHIBITED.

ZONE	REV.	DESCRIPTION	DATE	APPROVED
REVISIONS				

DATE	NAME	 Stratford, CT 06615 (203) 378-2659 The Electric Heater Company	
DRAWN	10/12/17		AMD
CHECKED			
ENG APPR.			
MFG APPR.			
Customer:			
Description:			
TYPICAL PIPING DIAGRAM MULTI NX HEATER / TANK			
SIZE	DWG. NO.	REV	
B		---	
SCALE: 1:1	FSCM: 19857	SHEET 1 OF 1	

DIMENSIONS ARE IN INCHES
 TOLERANCES:
 (UNLESS OTHERWISE SPECIFIED)
 FRACTIONAL ±¼
 ANGULAR: MACH ±½° BEND ±1°
 TWO PLACE DECIMAL ±0.01
 THREE PLACE DECIMAL ±0.005