

HATCO	HUBBELL	Booster Heater Description	
			
C-4	J64	n-	C 4KW
C-5	J65	n-	C-I
C-6	J66	n-	C 6KW
C-7	J67	n-	C 7KW
C-9	J69	n-	C 9KW
C-12	J612	n-	C-12KW
C-13	J613	n-	C-13.5KW
C-15	J615	n-	C 15KW
C-18	J618	n-	C-18KW
C-24	J624	n-	C 24KW
C-27	J627	n-	C 27KW
C-30	J630	n-	C-30KW
C-36	J636	n-	C 36KW
C-39	J639	n-	C 39KW
C-45	J645	n-	C 45KW
C-54	J654	n-	C-54KW
C-58	J658	-n-	C 58.5KW
			
S-6	J166	-Sn-	C 6KW
S-7	J167	Sn-	7KW C-
S-9	J169	Sn-	9K C-
S-12	J1612	Sn-	12KWC-
S-13	J1613	--Sn-	C-13.5KW
S-15	J1615	Sn-	15KWC-
S-18	J1618	Sn-	18KWC-
S-24	J1624	Sn-	24KWC-
S-27	J1627	Sn-	2o C-
S-30	J1630	Sn-	30KWC-
S-36	J1636	Sn-	36KWC-
S-39	J1639	Sn-	39KWC-
S-45	J1645	Sn-	45KWC-
S-54	J1654	Sn-	54KWC-
S-58	J1658	-Sn-	C-58.5KW

All Hubbell Models come STANDARD with ALL S/S Exterior and Brass PRV as well as an ALL S/S, ASME Stamped Tank with Foam Insulation and a 10 Year Non Pro-Rated Warranty.

Other standard features include: T&P gauge, T&P relief valve, electronic display controller w/low water & leak detection & plastic legs.

All J6 Models Models ship via UPS

Hubbell Voltage and Phase Model Number Suffix: (ie: J615R = 6 gallon, 15KW, 208V/3 phase)

RS - 208/1
R - 208/3
S - 240/1
T - 240/3
T4 - 480/3