

Master Specification: Model ETX Tankless

JOB NAME _____

ENGINEER _____

REPRESENTATIVE _____

CONTRACTOR _____

GENERAL

Provide a quantity of _____ packaged type instantaneous electric tankless water heater(s) Model No. **ETX** _____ as manufactured by HUBBELL Electric Heater Co., Stratford, CT. The entire unit is packaged ready for plumbing and electrical service connections.

HEATING CHAMBER

The heating chamber shall be all Sil-brazed copper and bronze construction. (**Optional Specification:** Type 316L Stainless Steel). A plastic heating chamber shall not be acceptable. Water heater heating chamber shall be rated for a maximum allowable working pressure of 150psi. The heating chamber and all electrical controls shall be completely enclosed in NEMA 4 enclosure suitable for wet/outdoor applications.

HEATING CAPACITY

The tankless heater shall be rated at _____ KW which will heat _____ GPM of water at _____ °F rise (_____ ° to 85 °F). Heaters that restrict hot water flow in any way or have a greater than 5psi pressure drop @ 23 GPM shall not be acceptable.

ELECTRICAL

The tankless heater shall be designed to operate at _____ volts, _____ phase, 50/60Hz balanced power and shall draw equal amperage across all phases at all times. For 3 phase heaters, power shall be a 3 wire (3 live, 1 ground) or a 4 wire (3 live, 1 neutral, 1 ground) system that does not require a neutral leg. The heater will draw _____ amps only when operating at full power. The immersion heating elements shall be high quality incoloy sheathed and sized to obtain the rated capacity. Each element is to be operated using zero cross over solid state controls. The heating elements shall be fully modulated from 0-100% to provide precise temperature control through the full range of flows. A Hi-Limit thermostat with automatic reset shall be factory installed to disconnect each heating element in the event of an over-temperature condition. An electronic digital display temperature controller shall be user adjustable in 1° increments in either °F or °C and shall display flow rate, outlet temperature, inlet temperature and provide error indication.

WARRANTY

Hubbell shall warranty all electrical components against defects in workmanship and material for a period of one (1) year from date of start-up, and the heating chamber for a full five (5) years from date of start-up, provided that the unit is started within three (3) months of date of shipment and installed and operated within the scope of the heater's design and operating capability. Labor is not covered under warranty. Each heater shall be shipped with a complete set of installation and operating instructions including spare parts list and approved drawings. All fabrication and assembly shall be performed in the U.S.A.

OPTIONS

In addition, the tankless electric water heater shall be supplied with the following options:

Option _____

Option _____

Option _____



Committed to continuous improvement..

Continuing research results in product improvement; therefore specifications are subject to change without notice. For the most updated information, consult the factory directly.

Made in the U.S.A.

