



Model MTX TANKLESS

Master Specification

SHIP NAME _____

ENGINEER / NAVAL ARCHITECT / SPECIFIER _____

SHIPYARD _____

CONTRACTOR / SHIP CHANDLER _____

General

Provide a quantity of _____ packaged type instantaneous electric tankless water heater(s) Model No. MTX_____ as manufactured by HUBBELL Electric Heater Co., Stratford, CT. The entire unit is packaged ready for plumbing and electrical service connections and shall be Type Approved by the American Bureau of Shipping (ABS) and bear the cULus listing mark certifying the entire unit to UL499, UL EPH Sanitation listed to ANSI/NSF Standard 5 and CSA C22.2 No. 64-M91 (single phase units) and CSA C22.2 No. 88 (three phase units).

Heating Chamber

The heating chamber shall be all sil-brazed copper and bronze construction. (Optional Specification: Type 316L Stainless Steel). A plastic heating chamber shall not be acceptable. Water heater heating chamber shall be rated for a maximum allowable working pressure of 100 psi. The heating chamber and all electrical controls shall be completely enclosed in a heavy gauge Type 304 stainless steel case.

Heating Capacity

The tankless heater shall be rated at _____ KW which will heat _____ GPM of water at _____ °F rise (_____ ° to _____ °F). Heaters that require the use of a flow restrictor or specialized aerator shall not be acceptable.

Electrical

The tankless heater shall be designed to operate at _____ volts, _____ phase, 50/60Hz balanced power and shall draw equal amperage across all phases at all times. For 3 phase heaters, power shall be a 3 wire (3 live, 1 ground) or a 4 wire (3 live, 1 neutral, 1 ground) system that does not require a neutral leg. The heater will draw _____ amps only when operating at full power. The immersion heating elements shall be high quality incoloy sheathed and sized to obtain the rated capacity. Each element is to be operated using zero cross over solid state controls. The heating elements shall be fully modulated from 0-100% to provide precise temperature control through the full range of flows. A Hi-Limit thermostat with automatic reset shall be factory installed to disconnect each heating element in the event of an over-temperature condition. An electronic digital display temperature controller shall be user adjustable in 1° increments in either °F or °C and shall display flow rate, outlet temperature, inlet temperature and provide error indication. A turbine-type flow meter shall be factory installed to provide precise temperature control for water flows as low as 0.2 GPM up to a maximum flow of 8 GPM. Heaters that require greater than 0.2 GPM flow for actuation or heaters that utilize on/off flow switch technology or restrict flow shall not be acceptable. (Optional Specification: High Flow Model MHX, provides up to 40 GPM flow with minimum actuation at 0.5 GPM).

Warranty

Hubbell shall warranty all electrical components against defects in workmanship and material for a period of one (1) year from date of start-up, and the heating chamber for five (5) years from date of start-up, provided that the unit is started within three (3) months of date of shipment and installed and operated within the scope of the heater's design and operating capability. Labor is not covered under warranty. Each heater shall be shipped with a complete set of installation and operating instructions including spare parts list and drawing. All fabrication and assembly shall be performed in the U.S.A.

Options

In addition, the water heater shall be supplied with the following options:

- Option _____
- Option _____
- Option _____

ISO 9001:2008



Committed to continuous improvements

Continuing research results in product improvement; therefore these specifications are subject to change without notice. For the most updated information, consult the factory.

Made in the U.S.A.



Hubbell™

Marine Products Division

The Electric Heater Company ■ P.O. Box 288 ■ Stratford, CT 06615-0288

Phone: 203-378-2659 ■ FAX: 203-378-3593 ■ info@hubbellheaters.com ■ www.hubbellheaters.com

Rev. A